




APPLIQUE • UDBI-068040

UP&DOWN



6W • 550 Lumen • 4000K

| | | | | | |
|-----------|---------------|-------------------------|----------------------|---------------------|---------------------------|
| RA | 30.000 | on off | I | IP65 | F |
| CRI>80 | Durata | ≥15.000 Accensioni | Classe di isolamento | Grado di Protezione | OK Superfici Infiammabili |



Caratteristiche generali

General characteristics / Caractéristiques générales / Obecné vlastnosti / Allgemeine Merkmale / Características generales / Geniká charaktiristiká

| | |
|--|---------------|
| Codice Articolo | UDBI-068040 |
| Item number / Code de l'article / Kód položky / Artikelcode / Código del artículo / Kodikós stoicheiou | |
| Codice EAN | 9090171006247 |
| EAN code / Code EAN / Kód EAN / EAN-Code / Código EAN / Kodikós EAN | |
| Tecnologia | LED |
| Technology / Technologie / Technologie / Tecnología / Tecnologia | |
| Tipologia | APPARECCHIO |
| Type / Type / Typ / Typ / Tipo / Τύπος | |
| Famiglia | APPLIQUE |
| Family / Famille / Rodina / Familie / Família / Οικογένεια | |
| Linea | UP&DOWN |
| Line / Ligne / Řádek / Linie / Línea / Grammi | |

Dimensioni

Dimensions and weight / Dimensions et poids / Rozměry a hmotnost / Abmessungen und Gewicht / Dimensiones y peso / Διαστάσεις και βάρος

| | |
|--|--------|
| Diametro | 80 mm |
| Diameter / Diamètre / Průměr / Durchmesser / Diámetro / Diámetros | |
| Spessore | 80 mm |
| Thickness / Épaisseur / Tloušťka / Dicke / Espesor / Páchos | |
| Diametro foro | 80 mm |
| Hole Diameter / Diamètre du trou / Průměr otvoru / Lochdurchmesser / Diámetro del agujero / Diámetros opón | |
| Peso netto | 411 gr |
| Net weight / Poids net / Čistá hmotnost / Nettogewicht / Peso neto / Katharó váρος | |

Imballo

Packing / Emballage / Obal / Verpackung / Embalaje / Syskevασία

| | |
|---|-----------|
| Inner Carton | 10 pz |
| Inner Carton / Carton Intérieur / Vnitřní karton / Innerer Karton / Caja de cartón interior / Εσωτερικό κουτί | |
| Master carton | 20 pz |
| Master Carton / Maître Carton / Vnější karton / Vorlagenkarton / Master Carton / Κύριο κουτί | |
| Peso lordo | 433 gr |
| Gross weight / Poids Brut / Hrubá hmotnost / Bruttogewicht / Peso bruto / Μεϊκτό βάρος | |
| Confezione | Color Box |
| Package / Emballage / Balík / Paket / Paquete / Πακέτο | |

Caratteristiche tecniche

Technical features / Caractéristiques techniques / Technické vlastnosti / Technische Merkmale / Características técnicas / Technická charaktiristiká

| | |
|---|-------------|
| Potenza effettiva | 6W |
| Effective power / Puissance effective / Efektivní výkon / Wirkleistung / Poder efectivo / Αποτελεσματική ισχύς | |
| Luminosità | 550 Lumen |
| Brightness / Luminosité / Jas / Helligkeit / Brillo / Lámpsi | |
| Colore luce | 4000K |
| Light color / Couleur claire / Barva světla / Helle Farbe / Color claro / Chróma fotós | |
| Apertura fascio | 7° - 100° |
| Beam opening / Ouverture du faisceau / Úhel vyzařování / Balkenöffnung / Apertura de la viga / Ανοίγμα δοκών | |
| Resa cromatica (CRI) | 80 |
| Color rendition (CRI) / Rendu des couleurs (Cri) / Ztvárnění barev (CRI) / Farbwiedergabe (CRI) / Rendimiento de color (CRI) / Παράδοσι chromáton (CRI) | |
| Dimmerabile | N |
| Dimmable / Dimmable / Strmívatelné / Dimmbare / Regulable / Με ροοστάτι | |
| Voltaggio | 220-240V/AC |
| Voltage / Tension / Napětí / Spannung / Voltaje / Τάση | |

Altre caratteristiche

| | |
|--|------------|
| Fattore di potenza | > 0,50 |
| Power factor / Facteur de puissance / Účinnost / Leistungsfaktor / Factor de potencia / Συνηλεστίσ ισχύος | |
| Frequenza | 50/60 Hz |
| Frequency / Fréquence / Kmitočet / Frequenz / Frecuencia / Sychnotita | |
| Corrente assorbita | 50 mA |
| Current consumption / Consommation actuelle / Spotřeba proudu / Stromverbrauch / Consumo actual / Τρέχουσα katanálosi | |
| Classe energetica | G |
| Energetic class / Classe énergétique / Energetická třída / Energieklasse / Clase de energia / Ενεργειακή κλάσι | |
| Durata ore | 30000 h |
| Duration / Durée / Trvání / Dauer / Duración / Diárkeia | |
| Cicli di accensione | 15000 |
| Ignition cycles / Cycles d'allumage / Spínací cykly / Zündzyklen / Ciclos de encendido / Κύκλοι ανάflexis | |
| Temperatura d'esercizio | -20 +40 °C |
| Operating temperature / Température de fonctionnement / Provozní teplota / Betriebstemperatur / Temperatura de funcionamiento / Thermokrasia leitourgias | |
| Grado protezione | IP65 |
| Degree of protection / Degré de protection / Stupeň ochrany / Schutzgrad / Grado de proteccion / Vathmós prostasias | |