

## Gizmo Solar Wall Light

GIZMO SOLAR WALL LIGHT  
0054041



### Product features

- Sleek and modern design solar outdoor wall light in black finish
- Integrated PIR sensor and daylight sensors
- Automatic light management - light up automatically when it gets dark after detecting any motion
- Easy installation - no direct mains wiring or connection required
- High lumen output - 290lm
- Long rated lifetime - 20,000 hours
- ON/OFF switch
- Robust construction - ABS housing
- Perfect for porch, garage, sheds, outhouses, outdoor office, garden fence, gate lighting
- Colour temperature - Cool White 4000K
- Fixing kit included
- Operating temperature: -10°C to 40°C



### NOTES

undefined

### PRODUCT OVERVIEW

Product name	GIZMO SOLAR WALL LIGHT
Technology	LED
Cap/Base	N/A
Housing	ABS Plastic
Mount	Wall surface mounted
General application	Residential & Consumer
ETIM Class	N/A
Warranty	3 years
Fixture luminous flux (lm)	290
Luminaire efficacy (lm/W)	64
Colour temperature (K)	4000
Light colour	Cool White
CRI (Ra)	80
Colour Variation Initial (SDCM)	SDCM6
Beam Angle (°)	100
Photobiological Risk Group	RG1
Electrical protection	Class III
Control gear type	LED driver constant current
Dimmable	No
Housing colour	Black
IP rating	IP54
IK rating	IK00
Product EAN number	5410288540412

## Gizmo Solar Wall Light

*GIZMO SOLAR WALL LIGHT*  
0054041

Dimming method	N/A
Light source included	INTEGRATED LED

### DATA TABLE

#### General data

Product name	GIZMO SOLAR WALL LIGHT
Technology	LED
Cap/Base	N/A
Housing	ABS Plastic
Mount	Wall surface mounted
General application	Residential & Consumer
Operating temperature range (°C)	-10°C - 40°C
Performance ambient temperature Tq (°C)	25
ETIM Class	N/A
Warranty	3 years

#### Optical data

Fixture luminous flux (lm)	290
Luminaire efficacy (lm/W)	64
Colour temperature (K)	4000
Light colour	Cool White
CRI (Ra)	80
Colour Variation Initial (SDCM)	SDCM6
Beam Angle (°)	100
Distribution type	Symmetric
Photobiological Risk Group	RG1

#### Electrical data

Mains voltage (V)	5V
Electrical protection	Class III
Control gear type	LED driver constant current
Dimmable	No
Drive current (mA)	1300
Glow Wire Test (°C)	650
Nominal Frequency (Hz)	N/A

#### Lifetime data

Lifespan L70 B50	20000
------------------	-------

#### Physical data

Housing colour	Black
IP rating	IP54
IK rating	IK00
Diffuser finish	Transparent
Diffuser material	Other
Reflector finish	White
Nominal Product Length (mm)	220

## Gizmo Solar Wall Light

*GIZMO SOLAR WALL LIGHT*  
0054041

Nominal Product Width (mm)	127
Nominal Product Height (mm)	90
Weight (kg)	0.452

### Packaging

Single packaging type	Carton
Product EAN number	5410288540412
Packaging single length / height (cm)	22.5
Packaging single width (cm)	10.0
Packaging single depth (cm)	13.5
DUN14 (outer)	15410288540419
Units per outer package	6
Packaging outer length / height (cm)	62.7
Packaging outer width (cm)	24.7
Packaging outer depth (cm)	29.4

### Safety data

Optimal operating condition (°C)	-10-40
----------------------------------	--------

## TECHNICAL DRAWINGS

