

NEW

PROIETTORI

SIRIO BT

12-36 V/DC

**12-36 V
AC/DC**

	A mm	B mm	C mm	g
20 W	120	115	24	250
30 W	155	125	24	350
50 W	200	165	33	600

OUTPUT

20 W	1.750 lm	110° ∠	S.E.L.V.	4000K		SRSBT-203640 NEW	1/16	€ 29,00
30 W	2.540 lm	110° ∠	S.E.L.V.	4000K		SRSBT-303640 NEW	1/16	€ 38,50
50 W	4.400 lm	110° ∠	S.E.L.V.	4000K		SRSBT-503640 NEW	1/16	€ 69,50



Corpo in PC anti invecchiamento, parabola bugnata ad elevata riflettanza. Vetro opale antiabbaglio, piastra in puro alluminio ad alto potere dissipante.

Anti-aging PC body, high reflectance embossed parabola. Anti-glare opal glass, pure aluminum plate with high dissipating power.

**S.E.L.V. (SRP)**

Safety Extra Low Voltage

Ideale in sistemi di videosorveglianza e sicurezza con pannelli fotovoltaici, su imbarcazioni, mezzi da cantiere e di soccorso.

Suitable for video surveillance and security systems with photovoltaic panels, on boats, construction and rescue vehicles.