




PANNELLI - P-QUADRO

BACKLIGHT



MOD. PQAB90


30 X 120



OUTPUT

42 W	3.600 lm	120°	220-240 V/AC 50/60 Hz	UGR < 19	4000K	PQAB-421240	1/4	€ 55,00
------	----------	------	-----------------------	----------	-------	--------------------	-----	---------

60 X 60



OUTPUT

42 W	3.600 lm	120°	220-240 V/AC 50/60 Hz	UGR < 19	4000K	PQAB-426040	1/4	€ 48,00
	4.100 lm	120°	220-240 V/AC 50/60 Hz	CRI > 90 - UGR < 19	4000K	PQAB90-426040	1/4	€ 53,00
	3.900 lm	120°	38-42 V/DC - 1000 mA C.C.*	UGR < 19 - No Driver - Diff. Prismatizzato	4000K	PQABUN-426060	1/4	€ 42,00

*Constant current

6 mm

Cornice ultraslim, solo 6 mm di spessore
Ultra slim frame, only 6 mm thickness

Pannelli da incasso a controsoffitto con tecnologia Backlight: l'impianto LED è installato sul retro del diffusore garantendo una migliore omogeneità luminosa.

Recessed ceiling panels with Backlight technology: the LED system is installed on the back of the diffuser ensuring better light uniformity.

Antingiamento - Anti-yellowing



DRIVER DIMMERABILE OPZIONALE /
OPTIONAL DIMMABLE DRIVER

42 W	DRIMPQ42	1/50	€ 40,00
	DRIMPQ40	1/50	€ 50,00
40 W	DRIMPQ42D	1/100	€ 54,00