




PAVI-078930




PAVI-1216030

PAVI




1 W	80 lm	24° ∠	24 V AC/DC	IP67- IK06	3000K	PAVI-014230	6/24	€ 36,00
					4000K	PAVI-014240		

Controcassa in policarbonato inclusa
Polycarbonate case included



3 W	240 lm	12° ∠	24 V AC/DC	IK06	3000K	PAVI-038930	1/6	€ 67,00
					4000K	PAVI-038940		
7 W	480 lm	12° ∠	24 V AC/DC	IK06	3000K	PAVI-078930	1/6	€ 70,00
					4000K	PAVI-078940		

Controcassa in policarbonato inclusa
Polycarbonate case included



12 W	840 lm	10° ∠	24 V AC/DC	IK08	3000K	PAVI-1216030	1/6	€ 120,00
					4000K	PAVI-1216040		

Controcassa in policarbonato inclusa
Polycarbonate case included

Incasso tondo calpestabile per installazione a pavimento. Anello e corpo in alluminio, vetro temperato, cavo in neoprene. Resistenza a pressione di 500 Kg.

Walkable round recessed light for floor installation. Aluminum ring and body, tempered glass, neoprene cable. Pressure resistance of 500 Kg.



Controcassa in policarbonato
Polycarbonate case



Alimentatori, connettori e accessori
Power supplies, connectors and accessories
PAG. 191