

Lynx SE

LYNX-SE 9W/840 2G7 SLV 10
0025902



Product features

- Single-bend pin base compact lamp, - Suitable for operation on electronic control gear (SE version), - For use with magnetic ballast (S Version), - Dimmable with suitable ballast, - Excellent colour rendering, - Suitable for emergency lighting



PRODUCT OVERVIEW

Product name	LYNX-SE 9W/840 2G7 SLV 10
Technology	Compact Fluorescent
Watt (Rated) (W)	9
Lamp shape	Other
Cap/Base	2G7
Lamp finish	Frosted/Coated
Fixture rating	Open
General application	Education, Hospitality, Logistics & Industry, Museums & Galleries, Office, Retail, Residential & Consumer
ETIM Class	EC000087
E-number FI	4944101
E-number SE	8357279
E-number Norway	3825332
Useful luminous flux (Fuse)	600
Luminous flux (lm)	600
Colour temperature (K)	4000
Light colour	Cool White
Colour Code	840
CRI (Ra)	82
Colour Variation Initial (SDCM)	SDCM5
Photobiological Risk Group	Not applicable
Wattage (W)	9
Dimmable	No
Dimming method	Mains: leading / trailing edge
Average life (Nominal) (h)	12000
Product EAN number	5410288259024

DATA TABLE

General data

Product name	LYNX-SE 9W/840 2G7 SLV 10
Technology	Compact Fluorescent
Watt (Rated) (W)	9
Lamp shape	Other

Lynx SE

LYNX-SE 9W/840 2G7 SLV 10

0025902

Cap/Base	2G7
Lamp finish	Frosted/Coated
Fixture rating	Open
General application	Education, Hospitality, Logistics & Industry, Museums & Galleries, Office, Retail, Residential & Consumer
ETIM Class	EC000087
E-number FI	4944101
E-number SE	8357279
E-number Norway	3825332

Optical data

Useful luminous flux (Fuse)	600
Luminous flux (lm)	600
Luminous flux (Rated) (lm)	600
Rated lamp efficacy 100h 50Hz at 25°C (lm/W)	67
Ambient temperature for maximum luminous flux (°C)	25
Colour temperature (K)	4000
Light colour	Cool White
Colour Code	840
CRI (Ra)	82
Colour Variation Initial (SDCM)	SDCM5
Adjustable chromaticity	N
Photobiological Risk Group	Not applicable
Rated lumen maint. factor (%) at 2000 h 50Hz	85
Rated lumen maint. factor (%) at 4000 h 50Hz	84
Rated lumen maint. factor (%) at 8000 h 50Hz	81

Electrical data

Wattage (W)	9
Starting time (max) (s)	10 Sec
Current (A)	0.17
Primary Supply/Product voltage - min (V)	198.0
Primary Supply/Product voltage - max (V)	240.0
Control gear required	Yes
Dimmable	No
Dimming method	Mains: leading / trailing edge
Lamp Energy Label (class)	G
kWh per 1000 hours burning time	9

Lifetime data

Average life (Nominal) (h)	12000
Average life (Rated) (h)	12000
Rated survival factor (%) at 2000 h 50Hz	96
Rated survival factor (%) at 4000 h 50Hz	90
Rated survival factor (%) at 6000 h 50Hz	80

Lynx SE

LYNX-SE 9W/840 2G7 SLV 10

0025902

Rated survival factor (%) at 8000 h 50Hz	72
Rated survival factor (%) at 12000 h 50Hz	62

Physical data

Nominal Product Length (mm)	152
Nominal Product Diameter (mm)	37
Max. Length base to base (mm) - A	152
Max. Lamp Diameter (mm) - D	13
Weight (kg)	0.026


Packaging

Product EAN number	5410288259024
Packaging single length / height (cm)	2.2
Packaging single width (cm)	3.8
Packaging single depth (cm)	15.9
DUN14 (inner)	25410288259028
Units per inner package	10
Packaging inner length / height (cm)	12.2
Packaging inner width (cm)	8.8
Packaging inner depth (cm)	18.0
DUN14 (outer)	15410288259021
Units per outer package	100
Packaging outer length / height (cm)	45.5
Packaging outer width (cm)	26.1
Packaging outer depth (cm)	19.5

Safety data

Lamp mercury content (mg)	2.5
Breakage cleaning instructions	Applicable
Recommendation for disposal at end of life	Applicable
Special purpose lamp	No
Dry applications use only	Yes
Suitable for household illumination	Yes

PHOTOMETRY




TECHNICAL DRAWINGS

Lynx SE
LYNX-SE 9W/840 2G7 SLV 10
0025902



0025902



9
kWh/1000h



2019/2015

SYLVANIA

Lynx SE

LYNX-SE 9W/840 2G7 SLV 10

0025902



0025902



9
kWh/1000h



2019/2015