



INC-OUTSIDER-1X15C

8031414864225

lumen

INC-OUTSIDER-1X15M

8031414864119


lumen

watt 1 x 15W

beam angle 24°

pf -

90 x 90 x pr. 96 mm



colour temp.

colour

1375 lm

1375 lm

INC-OUTSIDER-1X30C

8031414864256

lumen

INC-OUTSIDER-1X30M

8031414864133


lumen

watt 1 x 30W

beam angle 24°

pf -

116 x 116 x pr. 110 mm



INC-OUTSIDER-2X15C

8031414864232

lumen

INC-OUTSIDER-2X15M

8031414864126


lumen

watt 2 x 15W

beam angle 24°

pf -

174 x 90 x pr. 96 mm



colour temp.

colour

2750 lm

2750 lm

INC-OUTSIDER-2X30C

8031414864263

lumen

INC-OUTSIDER-2X30M

8031414864140


lumen

watt 2 x 30W

beam angle 24°

pf -

230 x 116 x pr. 110 mm



INC-OUTSIDER-3X15C

8031414864249

lumen

INC-OUTSIDER-3X15M

8031414864102


lumen

watt 3 x 15W

beam angle 24°

pf -

260 x 90 x pr. 96 mm



colour temp.

colour

4125 lm

4125 lm

INC-OUTSIDER-3X30C

8031414864270

lumen

INC-OUTSIDER-3X30M

8031414864157


lumen

watt 3 x 30W




beam angle 24°

pf -

335 x 116 x pr. 110 mm



Fotometria del prodotto / Photometric curve



Le curve fotometriche rappresentano il singolo modulo LED per ogni elemento / Above photometric curve represent the single module of each element

