

# ELITE

Faretto da incasso antiriflesso con struttura in alluminio e finitura in bianco goffrato. Luce spot orientabile.

Anti-glare recessed spotlight with aluminum frame and embossed white finish. Adjustable spot light.

## Materiale

alluminio

## Colore

bianco goffrato

## Temperatura colore

3000K / 4000K

## Driver

incluso

## Material

aluminum

## Colour

Embossed white

## Colour temperature

3000K / 4000K

## Driver

included



technical information ELITE



|                                                  | colour temp. | colour |  |
|--------------------------------------------------|--------------|--------|--|
| <b>INC-ELITE-1X10C</b><br>8031440363396<br>lumen | 1000 lm      |        |  |
| <b>INC-ELITE-1X10M</b><br>8031440363365<br>lumen | 1000 lm      |        |  |
| watt                                             | 10W          |        |  |
| beam angle                                       | 40°          |        |  |
| pf                                               | -            |        |  |
|                                                  | Ø 95 mm      |        |  |

|                                                  | colour temp. | colour |  |
|--------------------------------------------------|--------------|--------|--|
| <b>INC-ELITE-1X20C</b><br>8031440363372<br>lumen | 2000 lm      |        |  |
| <b>INC-ELITE-1X20M</b><br>8031440363341<br>lumen | 2000 lm      |        |  |
| watt                                             | 20W          |        |  |
| beam angle                                       | 40°          |        |  |
| pf                                               | -            |        |  |
|                                                  | Ø 107 mm     |        |  |

|                                                  | colour temp. | colour |  |
|--------------------------------------------------|--------------|--------|--|
| <b>INC-ELITE-1X30C</b><br>8031440363358<br>lumen | 2900 lm      |        |  |
| <b>INC-ELITE-1X30M</b><br>8031440363327<br>lumen | 2900 lm      |        |  |
| watt                                             | 30W          |        |  |
| beam angle                                       | 40°          |        |  |
| pf                                               | 0.90         |        |  |
|                                                  | Ø 150 mm     |        |  |

|                                                  | colour temp. | colour |  |
|--------------------------------------------------|--------------|--------|--|
| <b>INC-ELITE-1X45C</b><br>8031440363334<br>lumen | 4500 lm      |        |  |
| <b>INC-ELITE-1X45M</b><br>8031440363303<br>lumen | 4500 lm      |        |  |
| watt                                             | 45W          |        |  |
| beam angle                                       | 40°          |        |  |
| pf                                               | 0.90         |        |  |
|                                                  | Ø 150 mm     |        |  |

Fotometria del prodotto / Photometric curve

