

PROFESSIONALI  
**PAR56**



Ø176 x 110 mm - 940 g

30 W = 300 W	3.375 lm	4000 K	<b>PAR56-301640</b>	170,00 €
--------------	----------	--------	---------------------	----------

12 V
 
 IP68
 
 90°

TEMPERED GLASS

TECHNICAL NOTES

LAMPADA PER PISCINE IN VETRO TEMPERATO ANTI INVECCHIAMENTO  
ANTI-AGING TEMPERED GLASS POOL LAMP

INSTALLATION



INSTALLAZIONE RAPIDA CON MONTAGGIO A VITE  
QUICK INSTALLATION WITH SCREW MOUNT



PROFESSIONALI  
**PL-COVER**



E27

G24d

35 x 165 x 35 mm - 125 g

E27	10 W = 18 W	800 lm	120°	4000 K	<b>PLC-102740</b>	22,00 €
G24d 2 pin	10 W = 18 W	930 lm	180°	4000 K	<b>PLC-102440</b>	

220-240 V
 
 IP20

OPAL DIFFUSER

TECHNICAL NOTES

SI RACCOMANDA, PRIMA DELL'INSTALLAZIONE, DI RIMUOVERE  
OGNI ALIMENTATORE ELETTRONICO ED ELETTROMAGNETICO PRESENTE NEL CORPO ILLUMINANTE.  
BEFORE INSTALLING, IT IS RECOMMENDED TO REMOVE  
EACH ELECTRONIC AND ELECTROMAGNETIC BALLAST PRESENT IN THE LIGHTING FIXTURE.

NEW

PROFESSIONALI  
**GXLED**



Ø74 x 28 mm - 45 g

GX53	10 W = 80 W	1.000 lm	3000 K	<b>GXLED-105330</b> NEW	4,50 €
			4000 K	<b>GXLED-105340</b> NEW	

220-240 V
 
 IP20
 
 120°

PLASTIC HEATSINK
 
 OPAL PC DIFFUSER

TECHNICAL INDOOR

DECORATIVE

STRIP LED

TECHNICAL OUTDOOR

OUTDOOR

SOLAR

INDUSTRIAL

WORK

SORGENTI