



NEW
STRIP


ACCÈNTO PRO FLEX

NEW

STRIP

ACCÈNTO PRO FLEX

6 x 12



35 W (7 W/m)

950 lm (190 lm/m)

3000 K - 3500 K* - 4000 K

ACPFLEX5-07061200 **NEW**

79,00 €


24 V IP65 120° 5 METERS

3 STEP MACADAM CCT 128 LED/m DIMMABLE ≥90 CRI 30.000 HOURS 3 YEARS

TOTAL PARAMETERS

*3500 K
70 W (14 W/m)
1.800 lm (360 lm/m)

16 x 16



40 W (8 W/m)

1.950 lm (390 lm/m)

3000 K - 3500 K* - 4000 K

ACPFLEX5-08161600 **NEW**

139,00 €

24 V IP65 120° 5 METERS

3 STEP MACADAM CCT 120 LED/m DIMMABLE >90 CRI 30.000 HOURS 3 YEARS

TOTAL PARAMETERS

*3500 K
80 W (16 W/m)
3.600 lm (720 lm/m)

FOCUS

Rivestimento in silicone ad alta trasparenza, impermeabilità e uniformità
Silicone coating with high transparency, water resistance and uniformity


6 x 12 - TOP

6 x 12 - SIDE


16 x 16 - TOP

16 x 16 - SIDE

Flexibilità elevata per seguire linee morbide e forme personalizzate
High flexibility to follow smooth lines and custom shapes



r = 2,5 cm
Raggio di curvatura minimo solo su asse orizzontale
Minimum bending radius only on horizontal axis



r = 9 cm
Raggio di curvatura minimo su asse orizzontale o verticale
Minimum bending radius on horizontal or vertical axis


Tubo Led in silicone flessibile, progettato per seguire curve e forme personalizzate con continuità. Ideale per contorni, decorazioni e installazioni creative, offre un'illuminazione uniforme e un'ampia libertà di design, sia in interni che in esterni.

Flexible silicone LED tube, designed to seamlessly follow custom curves and shapes. Ideal for contours, decorations, and creative installations, it offers uniform lighting and ample design freedom, both indoors and outdoors.

TECHNICAL NOTES




REGOLAZIONE DEL COLORE LUCE TRAMITE COLLEGAMENTO ELETTRICO
LIGHT COLOR ADJUSTMENT THROUGH ELECTRICAL CONNECTION



N.B. IN QUESTA CONFIGURAZIONE, POTENZA E FLUSSO LUMINOSO VARIANO. CONSULTARE LA SEZIONE "PARAMETRI TOTALI" PER I VALORI SPECIFICI
IN THIS CONFIGURATION, POWER OUTPUT AND LUMINOUS FLUX VARY. REFER TO THE "TOTAL PARAMETERS" SECTION FOR SPECIFIC VALUES

OPTIONAL KIT



COMPATIBLE WITH

6 x 12 mm	ACPFLEX5-KIT06 NEW	10,00 €
16 x 16 mm	ACPFLEX5-KIT16 NEW	

IL KIT INCLUDE: 10 CLIPS IN ACCIAIO, UN TUBETTO DI COLLA SILICONICA, 2 TAPPI TERMINALI IN SILICONE E UNO STARTER DI ALIMENTAZIONE CON CAVO DA 30 CM
INCLUDED IN THE KIT: 10 STEEL CLIPS, A TUBE OF SILICONE GLUE, 2 SILICONE END CAPS AND A POWER STARTER WITH 30 CM CABLE

OPTIONAL PAG. 202-203

ALIMENTATORI E ACCESSORI
POWER SUPPLIES AND ACCESSORIES

TECHNICAL INDOOR

DECORATIVE

STRIP LED

TECHNICAL OUTDOOR

OUTDOOR

SOLAR

INDUSTRIAL

WORK

SORGENTI